

Product Name :
AC/DC Power Supply for Breadboard

Product Code :
CHINAELABC422002



Description :

AC/DC Power Supply for Breadboard

Technical Specification :

Signal bandwidth: 25MHz/60MHz/100MHz Real-time sampling rate: Max. 400Msps Equivalent sampling rate: Max. 10Gsps
5.6-inch TFT LCD Color display with better clearance, multicolor schemes available
With up to 2.4Mpts memory depth, more signal details can be seen.
Independent vertical scale and position control knobs for each channel
Edge, Pulse width and Video trigger mode available. Alternating triggering function is also available to stably display asynchronous signals
Unique variable trigger sensitivity to suit special measurement requirements on different occasions
Math functions including add, subtract, multiply and 1024- point FFT
Up to 24 kinds of parameters automatic measurements
Advanced cursor modes: Manual, Auto and Track
Practical low-pass, high-pass, band-pass, band-reject digital filters with adjustable cut-off frequency
Unique waveform recording and playback function.
PASS / FAIL detection, optical isolated PASS/FAIL output
Built-in 5 digital hardware frequency counter
Auto-calibration feature
Multiple language user interface
Pop-up menu, the user operation more convenient and intuitive
Embedded help information system in Chinese and English
Up to 10 internal setup and waveform files memories, external storage of setup, track, waveform, BMP bitmap and CSV files

USB Host Port, Support USB disk storage, and firmware upgrade can be carried out through an USB disk. PRINT button pressed to directly store the screen image (BMP) or the waveform data (CSV) in an USB disk
USB device and RS232C interface for the instrument remote control



Engineering Lab China