

**Product Name :**  
Asphalt Standard Viscometer

**Product Code :**  
CHINAELABC4650001



**Description :**

Asphalt Standard Viscometer

**Technical Specification :**

Asphalt Standard Viscometer is intended for testing the viscosity of liquid bitumen, coal pitch and flowing emulsified bitumen.

Technical Parameters

Power: AC 220V $\pm$ 10%, 50Hz

Circular tank: (1) Inner diameter: 160mm

(2) Depth: 116mm

Sample tube: 4 pieces in a set. The diameter of effuse tube are:  $\varnothing$ 10mm $\pm$ 0.025mm,  $\varnothing$ 5mm $\pm$ 0.025mm,  $\varnothing$ 4mm $\pm$ 0.025mm and  $\varnothing$ 3mm $\pm$ 0.025mm.

Ball plug specification: A: Diameter of ball: 12.7mm $\pm$ 0.05mm; Sign height: 92mm $\pm$ 0.25mm

B: Diameter of ball: 6.35mm $\pm$ 0.05mm; Sign height: 90.3mm $\pm$ 0.25mm

Temperature controlling range: 20 $\varnothing$ ~90 $\varnothing$

Temperature controlling accuracy:  $\pm$ 0.1 $\varnothing$

Timing resolution: 0.1~999.9s

Heating type: PTC tube electric heater (heating power is 750W)

Working temperature: -10 $\varnothing$ ~35 $\varnothing$

Relative humidity:  $\varnothing$ 85%

Dimension: length 420mm, width 340mm, height 570mm

Maximum power consumption: 800W



**Engineering Lab China**