

Product Name :
Asphalt Standard Viscometer

Product Code :
CHINAELABC4650001



Description :

Asphalt Standard Viscometer

Technical Specification :

Asphalt Standard Viscometer is intended for testing the viscosity of liquid bitumen, coal pitch and flowing emulsified bitumen.

Technical Parameters

Power: AC 220V \pm 10%, 50Hz

Circular tank: (1) Inner diameter: 160mm

(2) Depth: 116mm

Sample tube: 4 pieces in a set. The diameter of effuse tube are: \varnothing 10mm \pm 0.025mm, \varnothing 5mm \pm 0.025mm, \varnothing 4mm \pm 0.025mm and \varnothing 3mm \pm 0.025mm.

Ball plug specification: A: Diameter of ball: 12.7mm \pm 0.05mm; Sign height: 92mm \pm 0.25mm

B: Diameter of ball: 6.35mm \pm 0.05mm; Sign height: 90.3mm \pm 0.25mm

Temperature controlling range: 20 \varnothing ~90 \varnothing

Temperature controlling accuracy: \pm 0.1 \varnothing

Timing resolution: 0.1~999.9s

Heating type: PTC tube electric heater (heating power is 750W)

Working temperature: -10 \varnothing ~35 \varnothing

Relative humidity: \varnothing 85%

Dimension: length 420mm, width 340mm, height 570mm

Maximum power consumption: 800W



Engineering Lab China