

Product Name :
Proctor Needles Spring Type

Product Code :
CHINAELABC2690015



Description :

Proctor Needles Spring Type

Technical Specification :

Proctor needles are also called as the Proctor Penetrometers.

Proctor needles are utilized for the purpose of doing a quick evaluation of the maximum soil density in the field. The standard compaction curves that display the moisture contents against the densities are drawn in the laboratory utilizing the method of standard compaction.

Hence, the piercing of the proctor needles is corresponding.

Technical Specification:

The Proctor Needle comprises of the needle which comes attached to a spring-loaded plunger.

The stem of the spring-loaded plunger is calibrated to get a reading of 0 to 40 kgs in 1 kg division.

The longer stem is converted at every 12.5mm in order to read the depth of the penetration and for functioning with larger areas.

The small penetration stem is graded in the 12.5mm division and is utilized with the needles that are of smaller areas.

Needle points one each of 0.25, 0.5, 1.0, 1.5, 2.0, 3.5, and 6.0 sq.cm along with one tommy is also available.

Soil Testing Lab Equipment, tools, products and systems for engineering lab and engineering teaching vocational education. At Engineeringlabchina get practical educational equipment for Soil Testing Lab Equipment schools and teaching staff. Buy wholesale China Soil Testing Lab Equipment Manufacturers. Engineeringlabchina high quality Technical Education Equipment products at the best price from China. Soil Testing Lab Equipment China, Experiment Equipment suppliers China, and factory in China



Engineering Lab China