

Product Name :
Soil Extruder, Motor Operated**Product Code :**
CHINAELABC2690030**Description :**

Soil Extruder, Motor Operated

Technical Specification :

Features one of the largest capacities available on the market (ram stroke 900 mm), and due to the large number of standard adaptors, is considered the most versatile extruder.

The machine exerts a max. thrust of 60 kN and is very simple to operate: a lever controls the extruding speed and the hydraulic valve for the extrusion or return movement.

It can also be stopped at any point in its travel to enable extrusion into small smaller sample tubes or to take smaller size specimens.

Sampling tubes are held in place by an adjustable "V" shape bearing which can extrude either in the vertical or horizontal position.

Both the hydraulic cylinder assembly and the receiving table can easily be lowered alongside the machine to save space when not in use.

The machine is supplied without tube adaptors which have to be ordered separately.

Technical Specifications:

Power: 750 W

Max. load: 60 kN

Max. external diameter of sample tubes: 160 mm

Max. ram stroke: 900 mm

Max. working ram speed: 6 mm/sec.

Overall dimensions:

Horizontal working position(lxwxh): 2730x409x1180 mm

Soil Testing Lab Equipment, tools, products and systems for engineering lab and engineering teaching

vocational education. At Engineeringlabchina get practical educational equipment for Soil Testing Lab Equipment schools and teaching staff. Buy wholesale China Soil Testing Lab Equipment Manufacturers. Engineeringlabchina high quality Technical Education Equipment products at the best price from China. Soil Testing Lab Equipment China, Experiment Equipment suppliers China, and factory in China



Engineering Lab China