

Product Name :
Liquid Limit Devices Casagrande

Product Code :
CHINAELABC2690039



Description :

Liquid Limit Devices Casagrande

Technical Specification :

Casagrande method in mechanical form is known as liquid limit method and has been in use for soil mechanics for a number of decades.

The liquid limit data of soils is useful to correlate mechanical properties of soil, such as compressibility and lower shear strength.

Liquid limit is the water content at which soil passes from zero strength to an infinite strength, hence the true value of liquid limit cannot be determined.

For determination purpose liquid limit is that water content at which a part of soil, cut by a groove of standard dimensions, will flow together for a distance of 1.25cm under an impact of 25 blows in a standard liquid limit apparatus.

The soil at the water content has some strength which is about 0.17N/cm. sq. (17gms/sq.cm.).

At this water content soil just passes from liquid state to plastic state.

It consists on a brass cup held on an adjustable bracket.

The cup can be adjusted for a fall of 1 cm and can be raised and dropped on a rubber base of standard hardness by cam action.

A counter to register the number of blows.

Complete with one Casagrande grooving tool, one ASTM grooving tool and a height gauge block.

Soil Testing Lab Equipment, tools, products and systems for engineering lab and engineering teaching vocational education. At Engineeringlabchina get practical educational equipment for Soil Testing Lab Equipment schools and teaching staff. Buy wholesale China Soil Testing Lab Equipment Manufacturers. Engineeringlabchina high quality Technical Education Equipment products at the best price from China. Soil

Testing Lab Equipment China, Experiment Equipment suppliers China, and factory in China



Engineering Lab China